

1 2 3 4 5 6 7 8 9

ANGLE	± 5°	REV	LOCAS	DESCRIPTION	DESIGN	DATE	卫国峰
X.XXX	± 0.05	01			DRAWN	DATE	尚伟
X.XX	± 0.15	02			CHECKED	DATE	吴汉学
X.X	± 0.25	03			AUDITED	DATE	龚劲松
X	± 0.50	04			APPROVED	DATE	eric

Specifications/备注 (Remark)

Insulator:Black glass filled polyester
 PPS-GF30-FR
 Fiammability:UL94V-0
 Sleeve:Brass CuZn 36Pb3(36000)
 Contact clip(4 finger):Beryllium copper(C17200)
 Mating pin:Ø0.40 to 0.56mm
 Forces:(polished steel gauge Ø0.43mm)
 Insertion:2.0 N typ
 Withdrawal:1.0 N typ
 Mechancial life:min 500 cycles
 Rated current:1.0Amp
 Contact resistance:Max 10mΩ
 Dielectric resistance:Min 1000V RMS

ORDERING INFORMATION

R2630-2 XX X XG R 097 C 1

HEIGHT OF HOUSING:
30:3.0mm


NO.OF ARRAY PITCH
 0:NO PITCH
 4:7.62mm
 5:10.16mm
 6:15.24mm

NO.OF PINS PER ROW:
06-48P

CONTACT PLATING
 A=1U"
 B=2U"

 E=15U"
 F=30U"
 S=ORDINARY TIN PLATED
 H=HALF GOLD PLATED TIN

LENGTH OF TERMINAL



See page 33	No.of Positions	A	B	C	D
fig. 1	6	7.6	7.62	10.1	2.54/7.62
fig. 2	8	10.1	7.62	10.1	2.54/7.62
fig. 3	10	12.6	7.62	10.1	2.54/7.62
fig. 4	12	15.2	7.62	10.1	2.54/7.62
fig. 5	14	17.7	7.62	10.1	2.54/7.62
fig. 6	16	20.3	7.62	10.1	2.54/7.62
fig. 7	18	22.8	7.62	10.1	2.54/7.62
fig. 8	20	25.3	7.62	10.1	2.54/7.62
fig. 9	22	27.8	7.62	10.1	2.54/7.62
fig. 10	24	30.4	7.62	10.1	2.54/7.62
fig. 11	28	35.5	7.62	10.1	2.54/7.62
fig. 12	24	30.5	15.24	17.7	2.54/7.62
fig. 13	28	35.5	15.24	17.7	2.54/7.62
fig. 14	32	40.6	15.24	17.7	2.54/7.62
fig. 15	36	45.7	15.24	17.7	2.54/7.62
fig. 16	40	50.8	15.24	17.7	2.54/7.62
fig. 17	42	53.3	15.24	17.7	2.54/7.62
fig. 18	48	60.9	15.24	17.7	2.54/7.62

YLIES 东莞市瑞翔精密连接器有限公司
 DONG GUAN YLIES PRECISE CONNECTOR CO.,LTD

Tel:0769-85381995 / Fax:0769-85493987 / Email: ylies@ylies.cn / Web:www.ylies.cn


TITLE

291-2.54mm IC 圆孔排母 90度

DATE

2018-02-18

PROJECTON



REV A

UNIT mm

SCALE 1:1

PAGE 1/1

PART NO:

R2630-2XXXXGR097C1

DRAWING NO:

1 2 3 4 5 6 7 8 9