

ANGLE	± 5°	REV	LOCAS	DESCRIPTION	DESIGN	DATE	卫国峰
X.XXX	± 0.05	01			DRAWN	DATE	尚伟
X.XX	± 0.15	02			CHECKED	DATE	吴汉学
X.X	± 0.25	03			AUDITED	DATE	龚劲松
X	± 0.50	04			APPROVED	DATE	eric

NUMBER OF CONTACTS	Pitch	ROWS/Positions with Contacts
32 64	2.54	a b
16 32		a-
16 32	5.08 HALF-LOADED	a b ALL EVEN NO.



### Specifications/备注 (Remark)

#### 1-材料 (MATERIAL)

胶芯: PBT+30%G.F UL94V-0  
 Housing: PA6T+30%G.F UL94V-0  
 端子: 黄铜、磷铜、青铜  
 Contact: Brass, Phosphor, bronz

#### 2-特性 (characteristics):



额定电流: 3 AMP  
 Raring Current: 3 AMP .  
 接触阻抗: 30mΩ MAX.  
 Contact Resistance: 30mΩ MAX .  
 绝缘阻抗: 1000MΩMIN.  
 Insulating Resistance: 1000MΩMIN.  
 耐电压: AC 1000V.  
 Withstanding Voltage: AC 1000V.  
 温度范围: -55度至+105度  
 Temperature Range: -55°Cto +105°C



### ORDERING INFORMATION

**N-2 XX M S XX X X 1**

NO. OF PINS 16P Per Row 32P Per Row	TYPE S=180° R=90°	INSULATOR MATERIAL A: PBT B: PA6T C: PA9T	PACKING MATERIAL A: PE Bag B: TOPE&REED C: TUBE D: TRAY
DIN 41612	TYPE F=FEMALE M=MALE	CONTACT PLATING FULL OF GOLD SEMI-GOLD A0=0.8u" B0=0.8U"	
		A9=30u" B9=30U"	
		S1=ORDINARY TIN PLATED	
		S2=MATTE TIN PLATED	
		S3=TIN-PLATED HIGH-TEMPERATURE	



DIM"A"	2.50	4.00
--------	------	------

**YLIES** 东莞市瑞翔精密连接器有限公司  
 DONG GUAN YLIES PRECISE CONNECTOR CO.,LTD

TITLE: 315-2.54mm 欧式插针双排 180度 DATE: 2018-02-18

Tel: 0769-85381995 / Fax: 0769-85493987 / Email: ylies@ylies.cn / Web: www.ylies.cn

PROJECTON	REV	UNIT	SCALE	PAGE	PART NO:	DRAWING NO:
	A	mm	1:1	1/1	N-2XXMSXXXX1	