

ANGLE	± 5°	REV	LOCAS	DESCRIPTION	DESIGN	DATE	卫国峰
X.XXX	± 0.05	01			DRAWN	DATE	尚伟
X.XX	± 0.15	02			CHECKED	DATE	吴汉学
X.X	± 0.25	03			AUDITED	DATE	龚劲松
X	± 0.50	04			APPROVED	DATE	eric

Specifications/备注 (Remark)



1-材料 (MATERIAL)

胶芯: LCP UL94V-0
Housing:LCP UL94V-0
端子: 黄铜

Contact: Brass

2-特性 (characteristics):

额定电压: 250V AC/DC .
Voltage Rating:250V AC/DC .
额定电流: 5 AMP (AWG #22-28) .
Raring Current:5 AMP (AWG #22-28) .
接触阻抗: ≤10mΩ MAX.
Contact Resistance:≤10mΩ MAX.
绝缘阻抗: ≥1000MΩMIN.
Insulating Resistance:≥1000MΩMIN.
耐电压: 1500V AC/MINUTE
Withstanding Voltage:1500V AC/MINUTE
温度范围: -25度至+85度
Temperture Range: -25°Cto +85°C




PCB LAYOUT:COMPONENT SIDE

ORDERING INFORMATION

W30-XX XX X XX X

NO.OF PINS Per Row 02-12P	INSULATOR MATERIAL A:PA46 B:PA66 C:PA9T D:LCP	PACKING A:PE Bag B:TUBE C:TRAY
SERLES NO 30:3.0mm	CONTACT PLATING FULL OF GOLD SEMI-GOLD A0=0.8u" B0=0.8U" A9=30u" B9=30U" S1=ORDINARY TIN PLATED S2=MATTE TIN PLATED S3=TIN-PLATED HIGH-TEMPERATURE	CONACTL SHAPE S: Straight R: Right Angle LT:STRAIGHT SMT WT:RIGHT ANGLE SME



PART NO.	Dimension mm	
	A	B
W30-02XXXLTB	3.0	9.7
W30-03XXXLTB	6.0	12.7
W30-04XXXLTB	9.0	15.7
W30-05XXXLTB	12.0	18.7
W30-06XXXLTB	15.0	21.7
W30-07XXXLTB	18.0	24.7
W30-08XXXLTB	21.0	27.7
W30-09XXXLTB	24.0	30.7
W30-10XXXLTB	27.0	33.7
W30-11XXXLTB	30.0	36.7
W30-12XXXLTB	33.0	39.7

YLIES 东莞市瑞翔精密连接器有限公司
DONG GUAN YLIES PRECISE CONNECTOR CO.,LTD

Tel:0769-85381995 / Fax:0769-85493987 / Email: ylies@ylies.cn / Web:www.ylies.cn


TITLE

400-3.0mm 单排插针 卧贴

DATE

2018-02-18

PROJECTON



REV

A

UNIT

mm

SCALE

1:1

PAGE

1/1

PART NO:

W30-XXXXXWTB

DRAWING NO: